

Artículos**Reconocimiento y síntesis de voz (I)**

Evaluación del modelado acústico y prosódico del sistema de conversión texto-voz. <i>Cotovía Francisco Campillo, Eduardo Rodríguez</i>	5
Reconocimiento automático de emociones utilizando parámetros prosódicos. <i>Iker Luengo, Eva Navas, Inmaculada Hernández, Jon Sánchez</i>	13
New Advances in Cross-Task and Speaker Adaptation for Air Traffic Control Tasks. <i>Ricardo Córdoba, Javier Macías, Valentín Sama, Roberto Barra, José Manuel Pardo</i>	21
Main Issues in Grapheme-to-Phoneme Conversion for TTS. <i>Tatyana Polyakova, Antonia Bonafonte</i>	29

Análisis automático del contenido textual

NERUA: sistema de detección y clasificación de entidades utilizando aprendizaje automático. <i>Oscar Fernández, Zoraida Kozareva, Andrés Montoya, Rafael Muñoz</i>	37
Ánalisis de los fenómenos lingüísticos de los mensajes de correo electrónico en catalán desde la perspectiva de la traducción automática. <i>Joaquim Moret, Salvador Climent, Antoni Oliver, Mariona Taule</i>	45
Construcción y minimización eficiente de transductores de letras a partir de diccionarios con paradigmas. <i>Sergio Ortiz, Mikel L. Forcada, Gema Ramírez</i>	51
Evaluación de resúmenes automáticos mediante QARLA. <i>Enrique Amigó, Anselmo Peñas, Julio Gonzalo, Felisa Verdejo</i>	59

Traducción automática (I)

Modelo estocástico de traducción basado en N-gramas de tuplas bilingües y combinación log-lineal de características. <i>José B. Mariño, Rafael Banchís, Josep M. Crego, Adrià de Gispert, Patrik Lambert, José A. R. Fonollosa</i>	69
Traducción automática estadística basada en n-gramas. <i>Antoni Oliver, Gemma Boleda, Maite Melero, Toni Baldufa</i>	77
Algoritmo de Decodificación de Traducción Automática Estocástica basado en N-gramas. <i>Josep M. Crego, José B. Mariño, Adrià de Gispert</i>	85
Bilingual phrases for statistical machine translation. <i>Ismael García-Varea, Francisco Nevado, Daniel Ortiz, Jesús Tomás, Francisco Casacuberta</i>	93

Extracción y recuperación de información monolingüe y multilingüe

El tratamiento de la polísemia en la extracción de léxicos bilingües a partir de corpora paralelos. <i>Pablo Gamallo, Susana Sotelo</i>	103
Un entorno para el desarrollo y la evaluación de un sistema de búsqueda de respuestas en euskara. <i>Olatz Ansotegui, Xabier Arregi, Iñaki Esparza, Andoni Valverde</i>	111
Text Categorization using bibliographic records: beyond document content. <i>Arturo Montejo, Luis Alfonso Ureña, Ralf Steinberger</i>	119
Detección automática de spam utilizando regresión logística bayesiana. <i>M. Teresa Martín, Antonio J. Ortiz, Luis Alfonso Ureña, Miguel Ángel Gómez</i>	127

Lexicografía computacional

Exploitación computacional del metalenguaje en corpus especializados para la generación de diccionarios no convencionales. <i>Carlos Rodríguez</i>	137
Transforming a Constituency Treebank into a Dependency Treebank. <i>Alexander Gelbukh, Hiram Calvo, Sulema Torres</i>	145
Algoritmo de stemming para el gallego. <i>Miguel Rodríguez, Marisa Moreira, Angeles S. Plaices, Eloy Vázquez</i>	153
A Proposal for a Shallow Ontologization of Wordnet. <i>Salvador Climent, Jordi Atserias, Joaquim Moret, German Rigau</i>	161

Resolución de la ambigüedad léxica

Exploiting Rules for Word Sense Disambiguation in Machine Translation. <i>Lucía Specia, María das Gracas Volpe, Mark Stevenson</i>	171
Un Enfoque Integrado para la Desambigüación. <i>Jordi Atserias</i>	179
Uso flexible de soluciones evolutivas para tareas de Generación de Lenguaje Natural. <i>Raquel Hervás, Pablo Gervás</i>	187
Exploring the construction of semantic class classifiers for WSD. <i>Luis Villanueva, Lluís Márquez, German Rigau</i>	195

Semántica, pragmática y discurso

Nueva Técnica de Generación Automática de Gramáticas Para Sistemas de Diálogo. <i>Zoraida Callejas, Ramón López-Cáceres</i>	205
Dos aproximaciones basadas en reglas para la gestión del diálogo. <i>David Grilo, Lluís F. Hurtado, Emilio Sanchis, Encarna Segura</i>	213
Verificación de tema en sistemas de diálogo mediante la aplicación de un test de hipótesis bayesiano. <i>David Pérez-Piñar, Carmen García</i>	221
Utilización de medidas de confianza en sistemas de comprensión del habla. <i>Valentín Sama, Javier Ferreiro, Fernando Fernández, Rubén San, José Manuel Pardo</i>	229

Modelos lingüísticos, matemáticos y psicológicos del lenguaje

Evaluating the LIHLA lexical aligner on Spanish, Brazilian Portuguese and Basque parallel texts. <i>Helena de Medeiros, María das Gracas Volpe, Mikel L. Forcada</i>	237
Identificación de formas lógicas en el caso del español: propuesta de un modelo basado en reglas y aprendizaje automático. <i>Fernando Martínez, Miguel Ángel García</i>	245

Syntax-driven bindings of Spanish clitic pronoun <i>Ivan Vladimír Meza, Luis Alberto Pineda</i>	253
Diccionarios basados en taxonomías con estructura de grafo orientado acíclico <i>Antonio Ramón Vaquero, Francisco José Alvarez, Fernando Sáenz</i>	259
Reconocimiento y síntesis de voz (II)	
Comparación de modelos de lenguaje en tareas de transcripción automática de noticiarios televisivos <i>Francisco Javier Díez, Carmen García, Antonio Cardenal</i>	269
Analysis of prosodic features towards modelling of emotional and pragmatic attributes of speech <i>Jordi Adell, Antonio Bonafonte, David Escudero</i>	277
Un Sistema de Diálogo Multicanal para Acceder a la Información y Servicios de las Administraciones Públicas <i>Meritxell González, Marta Gattus</i>	285
Analisis y síntesis de expresión emocional en cuentos leídos en voz alta <i>Virginia Franciso, Pablo Gervás, Raquel Hervás</i>	293
Aplicaciones Industriales del PLN	
Una propuesta de infraestructura para el Procesamiento del Lenguaje Natural <i>Lorenza Moreno, Armando Suárez</i>	303
Hacia una arquitectura flexible para sistemas de predicción de palabras: propuesta de diseño y evaluación <i>Sira Elena Palazuelos, José Luis Martín, Líset Hierrezueto, Javier Macías</i>	311
A Named Entity Recognition System based on a Finite Automata <i>Muntzuri Padró, Lluís Padró</i>	319
Topic Identification based on Bayesian Belief Networks in the context of an Air Traffic Control Task <i>Fernando Fernández, Luis Fernando D'Haro, Javier Ferreiros, Juan Manuel Montero, Rubén Sanz</i>	327
Traducción automática (II)	
Clasificación y generalización de formas verbales en sistemas de traducción estocástica <i>Adrià de Gispert, José B. Mariño, Josep Mª Crego</i>	335
Sistema de Traducción Oral para el Castellano, Catalán e Inglés <i>Elisabet Comelles, Victoria Aranz, David Farwell</i>	343
Técnicas mejoradas para la traducción basada en frases <i>Marta Ruiz, José A. R.</i>	351
Computer-Assisted Translation using Finite-State Transducers <i>Jorge Civera, Elsa Cubel, Antonio Luis Lagarda, Francisco Casacuberta, Enrique Vidal, Juan Miguel Vilar</i>	357
Lingüística de corpus	
3LB-LEX: léxico verbal con frames sintáctico-semánticos <i>Montserrat Criví, Izaskun Alde Zahar, Eli Pociello, Mariona Taulé, Joan Aparicio, Lluís Márquez, Borja Navarro, Joan Castellví, María Antonieta Martí</i>	367
Designing an active learning based system for corpus annotation <i>Bertjan Busser, Roser Morante</i>	375
Uso del punto de transición en la selección de términos índice para agrupamiento de textos cortos <i>Héctor Jiménez, David Pinto, Paolo Rosso</i>	383
Una aproximación multilingüe a la clasificación de preguntas basada en aprendizaje automático <i>David Tomás, Empar Bibol, José Luis Vicedo, Armando Suárez, Lídia Moreno</i>	391
Gramáticas y formalismos para el análisis morfológico y sintáctico	
Generación automática de analizadores sintácticos a partir de esquemas de análisis <i>Carlos Gómez, Jesús Vilares, Miguel A. Alonso</i>	401
Tipología de errores gramaticales para un corrector automático <i>Ana Mª Diaz</i>	409
Evaluación del clustering de páginas web mediante funciones de peso y combinación heurística de criterios <i>Raquel Martínez, Víctor Fresno, Arantxa Casillas, Soto Montalvo</i>	417
Identifying Jargon in Texts <i>Stephen Helmreich, Jesús Llevadillo, David Farwell</i>	425
Proyectos	
VILE: Estudio acústico de la variación inter e intralocutor en español <i>Joaquim Llisterri</i>	435
The project HOPS: Enabling an Intelligent Natural Language Based Hub for the Deployment of Advanced Semantically Enriched Multi-channel Mass-scale Online Public Services <i>Marta Gattus, Meritxell González</i>	437
OAC-onto: Open Archive Cataloger, ontologías y metadatos <i>Inés Jacob, Joseba Abaitua, JosuKa Díaz, Fernando Quintana, Jon Fernández, Txus Sánchez</i>	439
Presentación del proyecto McLANGE (Multilingual eLearning in LANGUAGE Engineering) <i>Carme Colomina, Toni Badia</i>	441
El proyecto METIS-II <i>Toni Badia, Gemma Boleda, Maite Melero, Antoni Oliver</i>	443
Implementación de Sistemas de Diálogo en Dial-XML <i>Ramón López-Cózar, Zoraida Callejas, Miguel Gómez, Nuria Medina, Domingo Martín</i>	445
Demostraciones	
VENSES - A Linguistically-Based System for Semantic Evaluation <i>Delmonte Rodolfo</i>	449
Demuestra de una interfaz vocal para el control de un sistema de alta fidelidad <i>Fernando Fernández, Javier Ferreiros, Valentín Sama, Juan Manuel Montero, Rafael García</i>	451
Sistema de diálogo para el Proyecto DIHANA <i>Lluís F. Hurtado, Fernando Blat, Sergio Grau, David Grisol, Emilio Sanchis, Encarna Segarra</i>	453
TXALA un analizador libre de dependencias para el castellano <i>Jordi Asturias, Elisabet Comelles, Àngela Mayor</i>	455
GAG: Generación Automática de Gramáticas en un Sistema Conversacional de Interacción Oral <i>Zoraida Callejas, Ramón López-Cózar</i>	457
PHILIPS: Intelligent Speech Interpretation - la tecnología inteligente de reconocimiento de voz <i>Javier Viver</i>	459

XXI Congreso de la Sociedad Española para el Procesamiento del Lenguaje Natural



Universidad de Granada, 14-16 de Septiembre de 2005



I Congreso Español de Informática (CEDI 2005)



Universidad de Granada

EDITADO POR:

Ramón López-Cózar Delgado (Universidad de Granada)
L. Alfonso Ureña López (Universidad de Jaén)

COMITÉ CIENTÍFICO:

Presidentes:

Ramón López-Cózar Delgado (Universidad de Granada)
L. Alfonso Ureña López (Universidad de Jaén)

Miembros:

Prof. José Gabriel Amores Carredano (Universidad de Sevilla)
Prof. Toni Badia i Cardús (Universitat Pompeu Fabra)
Prof. Manuel de Buenaga Rodríguez (Universidad Europea de Madrid)
Prof.^a Irene Castellón Masalles (Universitat de Barcelona)
Prof.^a Arantza Díaz de Ilarrazá (Euskal Herriko Unibertsitatea)
Prof. Antonio Ferrández Rodríguez (Universitat d'Alacant)
Prof. Mikel Forcada Zubizarreta (Universitat d'Alacant)
Prof.^a Ana María García Serrano (Universidad Politécnica de Madrid)
Prof. Koldo Gojenola Galletebeitia (Euskal Herriko Unibertsitatea)
Prof. Xavier Gómez Guinovart (Universidade de Vigo)
Prof. Julio Gonzalo Arroyo (Universidad Nacional de Educación a Distancia)
Prof. José Miguel Goñi Menoyo (Universidad Politécnica de Madrid)
Prof. Joaquim Llisterri (Universitat Autònoma de Barcelona)
Prof. Ramón López-Cózar Delgado (Universidad de Granada)
Prof. Javier Macías Guarasa (Universidad Politécnica de Madrid)
Prof. José B. Mariño Acebal (Universitat Politècnica de Catalunya)
Prof.^a M. Antonia Martí Antonín (Universitat de Barcelona)
Prof. Lluís Padró (Universitat Politècnica de Catalunya)
Prof. Manuel Palomar Sanz (Universitat d'Alacant)
Prof. José Manuel Pardo Muñoz (Universidad Politécnica de Madrid)
Prof. Germán Rigau (Euskal Herriko Unibertsitatea)
Prof. Horacio Rodríguez Hontoria (Universitat Politècnica de Catalunya)
Prof. Kepa Sarasola Gabiola (Euskal Herriko Unibertsitatea)
Prof. L. Alfonso Ureña López (Universidad de Jaén)
Prof.^a M^a Felisa Verdejo Maillo (Universidad Nacional de Educación a Distancia)
Prof. Manuel Vilares Ferro (Universidade de Vigo)

REVISORES EXTERNOS:

Alicia Ageno, Pablo Daniel Agüero, Iñaki Alegria, Francesc Aliás, Laura Alonso, Javier Artiles, Xabier Artola, Zoraida Callejas, Rafael C. Carrasco, Montserrat Civit, Adrià de Gispert, Helanca Duxans, Nerea Ezeiza, David Farwell, Izaskun Fernández, Miguel Ángel García, Carmen García, Manuel García, José María Gómez, José Carlos González, Luis Hernández, Mikel Lersundi, Fernando Llopis, Fernando López, Pilar Manchón, Manuel J. Maña, Montserrat Marimon, María Teresa Martín, Patricio Martínez-Barco, José Luis Martínez, David Martínez, Fernando Martínez, Juan Manuel

Montero, Andrés Montoyo, Roser Morante, Asunción Moreno, Borja Navarro, Albino Nogueiras, Antoni Oliver, Víctor Peinado, Anselmo Peñas, Jesús Peral, Guillermo Pérez, Juan Antonio Pérez, Enrique Puertas, Eduardo Rodríguez, José Adrián Rodríguez, Maximiliano Saiz, Rubén San-Segundo, Mariona Taulé.

COMITÉ LOCAL

Presidente:

Ramón López-Cózar Delgado (Universidad de Granada)

Secretaria:

Zoraida Callejas Carrión (Universidad de Granada)

Miembros:

Prof.^a María V. Hurtado Torres (Universidad de Granada)
Prof. José María Guirao Miras (Universidad de Granada)
Prof.^a Nuria Medina Medina (Universidad de Granada)
Prof. Marcelino J. Cabrera Cuevas (Universidad de Granada)
Prof. Miguel Gea Megías (Universidad de Granada)

COLABORADORES

Maquetación de la revista:

Antonio F. Díaz García (Universidad de Granada)

Prólogo

El XXI Congreso de la Sociedad Española para el Procesamiento del Lenguaje Natural (SEPLN) se ha celebrado en el marco del Primer Congreso Español de Informática (CEDI 2005). Como en ediciones anteriores, con este evento la SEPLN ha pretendido promover la difusión de las actividades de investigación, desarrollo e innovación que realizan en cualquiera de los ámbitos del PLN los diversos grupos e investigadores españoles y extranjeros.

Esta edición del congreso se ha caracterizado, sin lugar a dudas, por la elevada participación de investigadores en sus diferentes facetas. En estas actas se recoge un total de 52 artículos (de los 74 presentados). Estos artículos han sido agrupados en la siguientes once áreas temáticas: *Reconocimiento y síntesis de voz, Análisis automático del contenido textual, Traducción automática, Extracción y recuperación de información monolingüe y multilingüe, Lexicografía computacional, Resolución de la ambigüedad léxica, Semántica, pragmática y discurso, Modelos lingüísticos, matemáticos y psicológicos del lenguaje, Aplicaciones industriales del PLN, Lingüística de corpus, y Gramáticas y formalismos para el análisis morfológico y sintáctico*.

Además, como es costumbre en este evento de la SEPLN, las actas dan cabida a un total de seis resúmenes de proyectos de investigación y seis resúmenes de demostraciones que, sin lugar a dudas, realzan aún más la calidad de las contribuciones.

Hemos contado también con la participación de un conferenciante invitado de una gran relevancia internacional en el PLN de forma oral, D. Michael F. McTear, de la *University of Ulster* (Irlanda del Norte).

Queremos aprovechar estas líneas para agradecer la colaboración de todos los miembros del Comité Científico en el proceso de revisión de trabajos, el cual ha sido particularmente difícil en esta ocasión dado la alta participación y el escaso margen de tiempo. Asimismo, queremos manifestar nuestra gratitud a todos los revisores externos por su colaboración activa en el proceso de revisión.

Finalmente, deseamos expresar nuestra gratitud a los miembros del Comité Local del XXI Congreso de la SEPLN y a la organización del Primer Congreso Español de Informática, por su importante apoyo logístico y humano en la organización de este evento de la SEPLN.

Esperamos que el Congreso sea provechoso a nivel científico y enriquecedor a nivel personal para los asistentes, y que la estancia en Granada les sea de su agrado.

Ramón López-Cózar Delgado
L. Alfonso Ureña López
Presidentes del Comité Científico del XXI Congreso de la SEPLN

Text Categorization using bibliographic records: beyond document content

Arturo Montejo-Ráez
 Dep. of Computer Science
 Universidad de Jaén
 Jaén, Spain
 amontejo@ujaen.es

L. Alfonso Ureña-López
 Dep. of Computer Science
 Universidad de Jaén
 Jaén, Spain
 laurena@ujaen.es

Ralf Steinberger
 IPSC
 Joint Research Center
 European Commission
 Ispra, Italy
 ralf.steinberger@jrc.it

Resumen: En este artículo se estudia el uso de diferentes fuentes de información para tareas de clasificación de textos. Dado el creciente número de bibliotecas digitales, se impone una revisión de la información disponible en dichas bases de datos. Se han llevado a cabo una serie de experimentos de clasificación multi-etiquetado dentro del dominio de la Física de Altas Energías haciendo uso de diferentes clasificadores base y combinando distintas fuentes de información. Los resultados muestran que el uso de metadatos es tan válido como el uso de versiones a texto completo de los documentos.

Palabras clave: clasificación automática de documentos, aprendizaje automático, bibliotecas digitales.

Abstract: This paper studies the use of different sources of information for performing a text classification task. The growing number of digital libraries imposes a review of the available data from those databases. Some experiments applying different base classifiers for a multi-label classifier in the domain of High Energy Physics on several of these possible sources have been carried out. Results show that the use of metadata is almost as good as the full-text version of papers.

Keywords: text categorization, machine learning, digital libraries.

1 Introduction

Corpora available for Text Categorization (Sebastiani, 2002) research tend to be not as accessible and complete as the research community wishes. Well known collections as *Reuters-21578*¹, *OHSUMED* (Hersh et al., 1994) (used in TREC evaluation forum) or *20 Newsgroups*² show, for each sample, sort fragments of text. Instead, within EUROVOC related experiments ((Bruno Pouliquen, Ralf Steinberger, and Camelia Ignat, 2003),(Ralf Steinberger, Johan Hagman, and Stefan Scheer, 2000) and (Ralf Steinberger, Bruno Pouliquen, and Johan Hagman, 2002)) full-text documents are used as sample data for classifiers training. But, in most of the experiments arranged based on these collections, just plain text data from main content of the document is used. Words are then stemmed or lemmatized, counted

and weighted following the same indexing scheme.

We have organized this paper by first providing a introduction to bibliographic metadata in CERN databases. Then, the design of the multi-label classifier is described specifying all the techniques involved. Since we want to prove that metadata sources can represent a very enriched source of information improving classification tasks, we have tested them against different classification schemes in order to validate the excelence of these type of sources without depending on specific learning algorithms. Later, the results obtained are listed using macroaveraging over documents for some of the best known evaluation measures. Finally, these results are dicussed and conclusions are reported.

2 Metadata

Data from digital libraries is much richer than just full-text versions of documents: digital libraries contain *metadata*, i.e. additional information about every stored document. Metadata is *data about data*: author of a document, date of publication, storing

¹Prepared by David D. Lewis. The collection is freely available from the web page <http://www.research.att.com/~lewis/reuters21578.html>

²Available at http://kdd.ics.uci.edu/databases/20newsgroups/20_newsgroups.tar.gz

format, identifier within the database, publisher, length and so on. The *Dublin Core Metadata Initiative*³ (DCMI) is a open standard for adding information to documents in digital libraries. The *Open Archive Initiative*⁴ (OAI) aims to establish a standard for document exchange between different digital libraries and a protocol for harvesting and retrieving of documents from database supporting it. OAI also support MARC⁵ format for metadata. DCMI is also used as a source of entities for the *Semantic Web*⁶ project (Berners-Lee, Hendler, and Lassila, 2001). As we can see, metadata is something to care about.

For High Energy Physics (HEP) related papers stored at CERN (Dallman and Le Meur, 1999; Montejo-Ráez and Dallman, 2001), the European Laboratory for Particle Physics (in Geneva, Switzerland), the MARC format is used (although full accessing through OAI has been recently integrated). A document record sample belonging to this database (CERN Document Server⁷) is shown in figure 1. We have prepared a corpus for our experiments that consists on what we call the *hep-ex* partition, since it is only about experimental Particle Physics. This partition contains 2967 documents and 2793 main keywords, and can be obtained by contacting the authors. These keywords come from human assignment by DESY experts by using the DESY HEPI thesaurus. The DESY Documentation group in Hamburg developed the HEPI (High Energy Physics Information) system from 1963 onwards. In this scheme all documents in the HEP field are indexed by subject specialists who read the entire articles. The thesaurus used contains approximately 2500 terms and has in general been updated every 1-2 years. The terms in this keyword list are used by the DESY Documentation Service for the indexing of papers on high energy (beam momentum above 400 MeV (per nucleon)) and particle physics, accelerator and detector technology and quantum field theory. Though the thesaurus proposes a two-level indexing, only labels on first level have been considered in our experiments, as an ap-

proach to reduce the high class imbalance reported by (Montejo-Ráez, Steinberger, and Ureña-López, 2004)). Manually assigned labels to sample document shown in figure 1 are listed in figure 2.

```
<?xml version="1.0" encoding="UTF-8"?>
<collection>

<dc xmlns="http://purl.org/dc/elements/1.1/"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://purl.org/dc/elements/1.1/
  http://www.openarchives.org/OAI/1.1/dc.xsd">

  <language>eng</language>

  <creator>Albrecht, H.</creator>

  <title>
    Determination of the Michel Parameters $rho$, $xi$, and $xi$ in $\tau$-Lepton Decays with $\tau \rightarrow \rho \nu_\tau$ Tags
  </title>

  <subject>
    Particle Physics - Experimental Results
  </subject>

  <identifier>
    http://preprints.cern.ch/ ... id=9711022
  </identifier>

  <description>Using the ARGUS detector at the $e^+e^- $ storage ring DORIS II, we have measured the Michel parameters $rho$, $xi$, and $xi$ for center of mass energies in the region of the $Upsilon$ resonances. Using $0.04 \pm 0.08$, $xi(e) = 1.12 \pm 0.20 \pm 0.09$, $xi_{mu} = 0.69 \pm 0.06 \pm 0.08$, $xi_{mu} = 1.25 \pm 0.27$ the combined ARGUS results on $rho$, $xi$, and $xi$ using this work on previous measurements.</description>

  <date>1997-12-01</date>

</dc>

</collection>
```

Figure 1: Sample for metadata information in XML DC format.

DESY HERA Storage
electron positron
experimental results
magnetic detector
Michel parameter
tau

Figure 2: Main DESY keywords manually assigned to sample at figure 1

We can see in those figure 1 the amount of additional data available. The target of this experiment is to test whether the use of additional data (apart from content data)

can improve classification to the profusion of current records of current answer is an improvement in classifiers.

3 Multi-labeling

TECAT stands for tool for building multi-label classifiers, assigning labels to a document (Montejo-Ráez, Steinberger, and Ureña-López, 2004). It is a tool for experimenters to build multi-labeled classifiers in a simple way.

TECAT is an open source and classification tool for building multi-label classifiers based on various algorithms. A better work can be given by the user involved in training with its related classifier.

1. Indexing

the task
tures (ter
document has been

- Stop words
- Working together on one item
- Terms have formal output. This is called

2. Folding

Folded 10-fold (Mitchell, 1997) stage adaption is

- The info kept empirical state
- The frequency

³<http://dublincore.org/>
⁴<http://www.openarchives.org>
⁵<http://www.loc.gov/marc/>
⁶<http://www.w3.org/2001/sw/>
⁷<http://cds.cern.ch>

lance re-
ger, and
igned la-
figure 1

```
./1.1/
  schema-instance
  ./elements/1.1/
  .xsd">
```

```
;ers $\rho$, $x_i$,
/s with $tan \rightarrow
```

sults

7/11/22

```
tor at the Se^+
e measured the
nd $x_i\delta$-
region of the
\pm 0.08$,
, $x_i\delta_{(e)}-
[\mu]= 0.69 \pm
\pm 0.27 the
$x_i$, and
vious
```

a information

is manually as-

```
: 1 the amount
  The target of
either the use of
  content data)
```

can improve classification performances. Due to the profusion of meta-data entries in the records of current digital libraries, a positive answer is an important clue to build enriched classifiers.

3 Multi-label classifier

TECAT stands for TExt CATegorization. It is a tool developed by authors for building multi-label automatic text classifiers, assigning more than one class per document (Montejo-Ráez, Steinberger, and Ureña-López, 2004). With TECAT you can experiment with different collections and classifiers in order to train an automatic multi-labeled text classifier.

TECAT implements the whole training and classification process for a multi-label classifier based on machine learning algorithms. A better look of the TECAT way-of-work can be given by describing every phase involved in training and classification along with its related parametrization.

1. Indexing. This phase corresponds to the task of selecting and filtering features (terms) that will represent each document. No multiwords identification has been considered:

- Stop words have been removed.
- Words have been truncated by passing them to the Porter's Stemming algorithm (Porter, 1997). From now onwards we refer to these resulting items as *terms* or *features*.
- Terms with less than 40 characters have been discarded, to avoid malformed long words (result of a bad output from the PDF converter). This number has been set empirically.

2. Folding. This stage performs a stratified 10-fold partitioning of the collection (Mitchell, 1997; Kohavi, 1995). At this stage additional filtering and feature selection is performed:

- The 50.000 terms with the highest information gain value have been kept. This limit has been chosen empirically from parallel experimentation.
- The classical TF.IDF term - frequency · inverse - document -

frequency (Salton and Buckley, 1988) weighting scheme has been used to weight features.

- Term weights in document vectors have been normalized using the cosine normalization (to force all vectors having the same norm).

3. Learning. This stage corresponds to learning algorithms (Lewis et al., 1996).

- The base algorithms used have been Rocchio, Widrow-Hoff (Lewis et al., 1996), PLAUM (Y. et al., 2002; S., S., and H., 2001) and Support Vector Machines (Joachims, 1998).
- A threshold has been computed according to the S-cut approach (Yang, 2001) and applied to Rocchio and Widrow-Hoff algorithms.
- The minimal value that the *F1* measure (van Rijsbergen, 1975; Lewis, 1991) must reach in order to consider the classifier as valid candidate (Montejo-Ráez, Steinberger, and Ureña-López, 2004) has been set to 0.1. With this approach, classes for which classifier are not enough performance are just discarded (we will just do not predict them).

For each of these algorithms, a different corpus of data has been used for learning and testing. Therefore, several corpora are produced as a combination of full-text information with available metadata:

- **Source A: Abstracts.** Experiments with given algorithms have been carried out on abstracts (the *description* field in XML DC form).
- **Source M: Metadata.** Each document is composed by a combination of content data (*abstract* and *title*) with fixed values (*date*, *subject*, *creator* and *language*).
- **Source F: Full-text.** The corpus is composed by the full-text version of documents (extracted from PDF versions of each paper).
- **Source F+M: Full-text and metadata.** This is the most complete corpus, where plain-text data is built up from full-text version, title and abstract, and

combined with fixed fields like *date*, *subject*, *creator* and *language*.

It is important to note that the processing of content data differs from that applied on metadata fields. These fields have been protected to not be affected by stop words removal and stemming procedures. For the rest of operations, each field is considered and additional feature.

1.233175 tau
1.533310 electron positron
0.327726 magnetic detector

Figure 3: Main DESY keywords automatically assigned by TECAT to sample at figure 1. They are preceded by their associated *Classification Status Value* (in this sample, returned by the PLAUM algorithm).

Three measures have been studied to determine whether a source outperforms another. These measures are *precision*, *recall* and *F1*. *F1* provides a more general view than precision and recall separately, being a common measure of the goodness of the method (though not very preferred in text processing tasks). However, precision and recall have been studied apart to inspect how a source affects them.

A sample of the output produced by TECAT is shown in figure 3. These labels have been selected automatically for sample given in figure 1. As we can see, just three keywords are selected by the classifier, with 100% of precision and 50% of recall, though.

4 Description of experiments and results

The description of experiments is described as follows: for each source (corpus), we have run four different experiments. Each of such experiments consists in using a different unique base classifier of the four mentioned before. As results, we will have sixteen sets of results. The reason to use different algorithms is to not be so dependent on the type of learning method used. Therefore, results for the four algorithms will be considered together and compared to those for experiments based on a different corpus. At each run the three measurements (precision, recall and *F1*) have been obtained for the ten most frequent keywords (see table 1).

Then, a Wilcoxon Signed Raked test has been carried out. This is a non-parametric

experimental results	
magnetic detector	
talk	
electron positron	
quark	
CERN LEP Stor	
anti-p p	
Z0	
Batavia TEVATRON Coll	
mass spectrum	

Table 1: Ten most frequent categories

on rec.	A
A	0.99
M	0.99
F	0.99
F+M	0.99

Table 3: Ta

on F1	A
A	0.5
M	0.9
F	0.9
F+M	0.9

Table 4: T

test that let us know if two distributions on the same variable are statistically different. We have used *Octave*⁸ to compute the *p-values* returned by the test. In our comparison, we will consider only *p*-values under 0.05, that is, the probability for the two given distributions to differ not by chance is higher than 95%. Since we have run a 10-fold cross-validation mechanism within TECAT, we have averaged the measured values of precision, recall, *F1* and accuracy for the ten most frequent keywords. Therefore, to compare source A (abstracts) against source F (full-text), we created two distributions with 40 values each (4 algorithms \times 10 measured keywords). Then, we could construct the comparison matrices (one per measure) with Wilcoxon *p*-values shown at tables 2, 3 and 4.

By looking at those tables we can determine the confidence that two source strategies are different. For example, as seen on table 2, the Wilcoxon test found a *p*-value of 0.000045 between strategies F+M and A. We can interpretate this value as a confidence of 99.9965% that the two distributions are different (based on precision measurements in this case). Besides, because of the tailored nature of our test, this measure also indicates the confidence on asserting that strategies in columns are *better* than strategies in rows.

on prec.	A	M	F	F+M
A	0.5000	0.0627	0.00014	0.000045
M	0.9372	0.5000	0.0790	0.026
F	0.9998	0.9200	0.5000	0.09387790
F+M	0.9999	0.9735	0.9061	0.5000

Table 2: Tailored Wilcoxon test over precision

⁸Octave is a high-level language, primarily intended for numerical computation that is available under the GPL. <http://www.octave.org>

Wilcoxon tailored. To conclude if a difference anything about provides better of data. The tailored analysis source output how it has tables.

The main obtained in table 5. At this measures of performance by using a single entry WH M averaged values based on the Hoff algorithm thresholding duration described.

Many classes) is due to fact that trained with percentage confidence about it different algorithms some classes how, performing considering all classifiers only trained algorithms (produced set of performance wider range of choice).

5 Analysis

First, we report experiments: t

<i>on rec.</i>	A	M	F	F+M
A	0.5000	0.00000002	0.0018	0.000001
M	0.9999	0.5000	0.9997	0.7318
F	0.9981	0.00023	0.5000	0.000001
F+M	0.9999	0.2681	0.9999	0.5000

Table 3: Tailored Wilcoxon test over recall

<i>on F1</i>	A	M	F	F+M
A	0.5	0.0000001	0.000018	0.0000008
M	0.9	0.5000	0.9766	0.2217
F	0.9	0.0233	0.5000	0.0000007
F+M	0.9	0.7782	0.9999	0.5000

Table 4: Tailored Wilcoxon test over F1

Wilcoxon can be one-tailored or two-tailored. For one-tailored test we can conclude if a difference exists, but we cannot say anything about the *direction* of it. It is our interest to find if a certain source of data provides better results over another source of data. Thus, we are interested in a one-tailored analysis that will let us know if one source outperforms another source. This is how it has been computed in the given tables.

The macroaveraged values by document obtained in our experiments are given in table 5. At this table, each row shows the measures of performance for a given algorithm by using a given source. For example, the entry *WH M* specifies measured macroaveraged values by document using the metadata based corpus as source and applying Widrow-Hoff algorithm as base classifier (with S-cut thresholding as detailed previously in configuration description).

Many classes are just discarded (column % classes) in the filtering process or due to fact that no possible algorithm can be trained with a minimum performance (the percentage column provides useful information about it). It is interesting to note how different algorithms are more "trainable" on some classes than others at this point. Anyhow, performance measures are obtained considering all classes covered by the corpus, not only trained ones. It is significative how some algorithms (PLAUM and SVM) which a reduced set of candidate classes report as good performance as other algorithms covering a wider range of classes (Widrow-Hoff and Rocchio).

5 Analysis of results

First, we remind the target of these experiments: to study how the use of differ-

Prec.	Recall	F1	% classes	Experiment
0.4429	0.5403	0.4553	84,43	WH A
0.4412	0.5555	0.4641	85,00	WH F
0.4553	0.5534	0.4663	84,54	WH M
0.4639	0.5713	0.4805	87,27	WH F+M
0.4711	0.5421	0.4611	88,16	Rocchio A
0.4272	0.5235	0.4281	86,12	Rocchio F
0.4525	0.5605	0.4569	86,18	Rocchio M
0.4424	0.5419	0.4432	87,92	Rocchio F+M
0.6911	0.4104	0.4895	52,48	PLAUM A
0.7106	0.4348	0.5118	57,87	PLAUM F
0.7201	0.4486	0.5266	55,67	PLAUM M
0.7254	0.4529	0.5314	59,27	PLAUM F+M
0.7458	0.3336	0.4342	31,14	SVM A
0.7549	0.3574	0.4590	35,03	SVM F
0.7734	0.3516	0.4586	32,23	SVM M
0.7697	0.3732	0.4775	36,62	SVM F+M

Table 5: Macroaveraged measures for all classes in performed experiments

ent sources of data affects performance of a multi-label categorization engine. Not only is interesting to find which combinations of sources are best, but also to study whether is worth using one over another. For example, the computational cost of using full-text documents is much higher than that of using just small abstracts: the collection is smaller, the trained data demands lower storage space, and the classification process is sped up. Thus, it is very important, in our domain, to identify such facts.

To understand these results we can notice at table 4, for instance, that the p-value corresponding to row F and column F+M is very small: 0.0000007. It says that when using the corpus created as combination of full-text and metadata, we can be sure (99.99993% sure!) of obtaining more accurate results than those obtained from corpus based on just full-text data. We also find that the p-value shows a *transitive* behaviour: let a , b and c be distinctive sources, and ' $>$ ' a binary operator to indicate that a source provides better results than another, then, we can state that:

$$(a \geq b) \wedge (b \geq c) \implies a \geq c \quad (1)$$

At table 4 M outperforms A, and F+M outperforms M, therefore, we can see that F+M outperforms widely A.

It is possible to illustrate graphically the improvement obtained when using some sources instead of others. Figures 4, 5 and 6 show the effect, per measure, of each source. At each diagram the considered

gories

itions on different. e the p- our com- values un- r the two chance is a 10-fold TECAT, ucs of pre- r the ten e, to com- . source F tions with measured struct the (sure) with s 2, 3 and

can deter- strate as seen on 1 a p-value M and A. confidence butions are measurements the tailored lso indicates strategies in ; in rows.

F+M
0.000045
0.026
0.09387790
0.5000

t over preci-

, primarily in- hat is available org




Figure 4: Comparison of sorted measures for each source over precision




Figure 5: Comparison of sorted measures for each source over recall

sources are drawn, with their 40 measured values sorted to ease the visual comparison between sources. Consequently, each source series is composed by 40 points. In principle, the use of only the abstract of a document seems to be the worst choice. Actually, this is not an easy question, as we will argue from Wilcoxon test results.

As said before, we can notice an increment in performance just having a look at those diagrams, but the statistical values contained in tables 2, 3 and 4 provide solid evidences on the studied subject.




Figure 6: Comparison of sorted measures for each source over F1

6 Conclusions

By reviewing one table after the other we can conclude the following points:

1. The combined use of metadata and full-text information is the best choice in any case (though the most costly).
2. Metadata is also good choice in most cases despite the fact that it is outperformed by the combination of full-text and metadata when we are more interested in precision.
3. Metadata source even outperforms corpus based on full-text papers for recall and F1.
4. As main conclusion, the metadata source should be preferred due to its reduced computational cost and its good behaviour against full-text and (except for precision matters) combined full-text and metadata.

Therefore, adding a big full-text content of a document (extracting it from the PDF version) to the features that can be promptly extracted from the document record stored in the database is not worthy. This conclusion validates the visual conclusion obtained from inspecting previous diagrams, where we can see how the curve for the metadata source is usually above the rest of curves. This effect is less clear for precision, as reported by the test.

7 Acknowledgments

This work is partially funded by the Minister of Science and Innovation of Spain and project TIN2006-15208.

References

Berners-Lee, Tim, Hendler, James, Lassila, Ora. 2001. The Semantic Web. Scientific American, 284(5), 34-43.

Bruno Pouliot, Camelia Ionescu, and Ion Todirascu, 2006. Semantic Annotation of XML Data Using the 'OntoXtractor' tool. In 'The Semantic Web - ISWC 2006', Bucharest, Romania, October 2006, pp. 103-117.

Dallman, David, 1999. Autonomic Computing: A Physiological Approach. IBM Laboratory, Zurich Research Laboratory, Switzerland.

Hersh, William, and David Johnson, 1998. Interactive Large-Scale Text Retrieval. In 'Proceedings of the Annual ACM SIGIR Conference on Information Retrieval', New York, USA, pp. 1-8.

Joachims, Thorsten, 1998. Text Categorization with Support Vector Machines. In 'Proceedings of the 14th International Conference on Machine Learning', Nédellec, France, June 1998, pp. 160-169.

Kohavi, Ron, 1995. A Study and Validation of Cross-Validation Estimation Techniques for Performance Measurement. In 'the Fourteenth International Conference on Machine Learning', Morgan Kaufmann Publishers, San Francisco, CA, pp. 1137-1145.

Lewis, D. D., 1997. Naive Bayes for Text Classification. In 'Natural Language Processing', Morgan Kaufmann Publishers, San Francisco, CA, pp. 318-331.

7 Acknowledgements

This work is partially financed by the Spanish Minister of Science and Technology, by means of project TIC2003-07158-C04-04.

References

- Berners-Lee, Tim, James Hendler, and Ora Lassila. 2001. The Semantic Web. *Scientific American*, 284(5):34–43, May.
- Bruno Pouliquen, Ralf Steinberger, and Camelia Ignat. 2003. Automatic Annotation of Multilingual Text Collections with a Conceptual Thesaurus. In Amalia Todirascu, editor, *Proceedings of the workshop 'Ontologies and Information Extraction' at the EuroLan Summer School 'The Semantic Web and Language Technology'(EUROLAN'2003)*, page 8 pages, Bucharest (Romania).
- Dallman, David and Jean-Yves Le Meur. 1999. Automatic keywording of high energy physics. Technical report, European Laboratory for Particle Physics, Geneva, Switzerland, October.
- Hersh, William, Chris Buckley, T. J. Leone, and David Hickam. 1994. Ohsumed: an interactive retrieval evaluation and new large test collection for research. In *Proceedings of the 17th annual international ACM SIGIR conference on Research and development in information retrieval*, pages 192–201. Springer-Verlag New York, Inc.
- Joachims, Thorsten. 1998. Text categorization with support vector machines: learning with many relevant features. In Claire Nédellec and Céline Rouveiro, editors, *Proceedings of ECML-98, 10th European Conference on Machine Learning*, number 1398, pages 137–142, Chemnitz, DE. Springer Verlag, Heidelberg, DE.
- Kohavi, Ron. 1995. A study of cross-validation and bootstrap for accuracy estimation and model selection. In *Proc. of the Fourteenth International Joint Conference on Artificial Intelligence*, pages 1137–1145. Morgan Kaufmann, San Mateo, CA.
- Lewis, D. D. 1991. Evaluating Text Categorization. In *Proceedings of Speech and Natural Language Workshop*, pages 312–318. Morgan Kaufmann.
- Lewis, David D., Robert E. Schapire, James P. Callan, and Ron Papka. 1996. Training algorithms for linear text classifiers. In Hans-Peter Frei, Donna Harman, Peter Schäuble, and Ross Wilkinson, editors, *Proceedings of SIGIR-96, 19th ACM International Conference on Research and Development in Information Retrieval*, pages 298–306, Zürich, CH. ACM Press, New York, US.
- Mitchell, Tom M.. 1997. *Machine Learning*, chapter Decision tree learning, pages 55–59. McGraw-Hill, New York.
- Montejo-Ráez, A., R. Steinberger, and L. A. Ureña-López. 2004. Adaptive selection of base classifiers in one-against-all learning for large multi-labeled collections. In Vicedo J. L. et al., editor, *Advances in Natural Language Processing: 4th International Conference, EsTAL 2004*, number 3230 in Lectures notes in artificial intelligence, pages 1–12. Springer.
- Montejo-Ráez, Arturo and David Dallman. 2001. Experiences in automatic keywording of particle physics literature. *High Energy Physics Libraries Webzine*, (issue 5), November. URL: <http://library.cern.ch/HEPLW/5/papers/3/>.
- Porter, M. F.. 1997. *An algorithm for suffix stripping*, pages 313–316. Morgan Kaufmann Publishers Inc.
- Ralf Steinberger, Bruno Pouliquen, and Johan Hagman. 2002. Cross-lingual Document Similarity Calculation Using the Multilingual Thesaurus EUROVOC. *Third International Conference on Intelligent Text Processing and Computational Linguistics*.
- Ralf Steinberger, Johan Hagman, and Stefan Scherer. 2000. Using thesauri for automatic indexing and for the visualisation of multilingual document collections. pages 130–141.
- S., Robertson, Walker S., and Zaragoza H. 2001. Microsoft cambridge at trec-10: filtering and web tracks. In *Text Retrieval Conference (TREC-10)*.
- Salton, G. and C. Buckley. 1988. Term weighting approaches in automatic text retrieval. *Information Processing and Management*, 24(5):513–523.

Resum
deseado
automá
han apl
y el al
estudio
filtrado
resultac
rápido
Palab

Abstra
Regres:
also us
Our air
show g
algorith
Keywo

I Intro

El uso del s
sufrido en los
Actualmente
afecta tanto
electrónicos
través de Inte
deseado o S
proporciona
medio de lleg
un coste muy
Estudios i
importancia i
filtrado de dic
Australian Co

- Sebastiani, Fabrizio. 2002. Machine learning in automated text categorization. *ACM Comput. Surv.*, 34(1):1-47.
- van Rijsbergen, C. J. 1975. *Information Retrieval*. London: Butterworths. <http://www.dcs.gla.ac.uk/Keith/Preface.html>.
- Y., Li, Zaragoza H., Herbrich R., Shawe-Taylor J., and Kandola J. 2002. The perceptron algorithm with uneven margins. In *Proceedings of the International Conference of Machine Learning (ICML'2002)*.

- Yang, Yiming. 2001. A study on thresholding strategies for text categorization. In W. Bruce Croft, David J. Harper, Donald H. Kraft, and Justin Zobel, editors, *Proceedings of SIGIR-01, 24th ACM International Conference on Research and Development in Information Retrieval*, pages 137-145, New Orleans, US. ACM Press, New York, US. Describes RCut, Scut, etc.

Lexicografía computacional	163
Extracción de relaciones léxico-semánticas a partir de palabras derivadas usando patrones de definición <i>Eneko Aguirre, Mikel Lersundi</i>	165
Etiquetación robusta del lenguaje natural: procesamiento y segmentación <i>Jorge Graña Gil, Fco. Mario Barcala Rodríguez, Jesús Vilares Ferro</i>	173
Generación automática de familias morfológicas mediante morfología derivativa productiva <i>Jesús Vilares, David Cabrero, Miguel A. Alonso</i>	181
Internet como fuente de información léxica: extracción de etiquetas de dominio y detección de nuevos sentidos <i>Julio Gonzalo Arroyo</i>	185
Resolución de la ambigüedad léxica	197
A POS-Tagger generator for unknown languages <i>Nuno C. Marques, Gabriel Pereira Lopes</i>	199
Estudio de cooperación de métodos de desambiguación léxica: marcas de especificidad vs. máxima entropía <i>Armando Suárez, Andrés Montoyo</i>	207
Evaluación de un etiquetador morfosintáctico basado en bigramas especializados para el castellano <i>Ferran Pla, Antonio Molina, Natividad Prieto</i>	215
Reconocimiento y síntesis de voz	223
Asignación automática de marcas de pitch basada en programación dinámica <i>Francesc Alias Pujol, Ignasi Iriondo Sanz</i>	225
Modelo cuantitativo de entonación del español <i>David Escudero Mancebo, Valentín Cardenoso Payo</i>	233
Transcriptor ortográfico-fonético para el castellano <i>Maria José Castro, Salvador España, Ismael Salvador, Andrés Marzalz</i>	241
Text to speech — a rewriting system approach <i>José João Almeida, Alberto Manuel Simões</i>	247
Una nueva técnica para evaluar sistemas conversacionales basada en la generación automática de diálogos <i>R. López-Cózar, J. C. Segura, A. De la Torre, A. J. Rubio</i>	255
Análisis automático del contenido textual	263
Categorización de textos multilingües basada en Redes Neuronales <i>Manuel García Vega, Maite Martín Valdivia, L. Alfonso Ureña López</i>	265
Cross-lingual keyword assignment <i>Ralf Steinberger</i>	273
Generación automática de resúmenes personalizados <i>Ignacio Acero, Matías Alcojor, Alberto Díaz, José María Gómez, Manuel Maña</i>	281
Proyectos	
Proyecto europeo D'Homme <i>José F. Quesada, J. Gabriel Amores</i>	291
XML-Bi: Procesamientos para gestión de flujo documental multilingüe sobre XML/TEI <i>Joseba Abaitua, Arantza Domínguez, Carmen Isasi, José Luis Ramírez, Inés Jacob, Idoia Madariaga, Arantza Casillas, Raquel Martínez, Alberto Garay, Thomas Diedrich</i>	293
Proyecto de indexado automático para documentos en el campo de la física de altas energías <i>Arturo Montejo Ráez</i>	295
Proyecto Tagparsing <i>J. Gabriel Amores</i>	297
Hermes: Servicios de personalización inteligente de noticias mediante la integración de técnicas de análisis automático del contenido textual y modelado de usuario con capacidades bilingües <i>Alberto Díaz, Manuel de Buenaga, Ignacio Giráldez, José María Gómez, Antonio García, Inmaculada Chacón, Beatriz San Miguel, Enrique Puertas, Raúl Murciano, Matías Alcojor, Ignacio Acero, Pablo Gervás</i>	299
Spanish Acquisition: Analysis of learner corpora generated through inter-cultural telecollaboration <i>Julia Kushner, James Lantolf, Steven Thorne, Antonio Jiménez, Brenda Ross, Sagrario Salaberri</i>	301
Proyecto europeo Siridus <i>José F. Quesada, J. Gabriel Amores</i>	303
XTRA-Bi: Extracción automática de entidades bitextuales para software de traducción asistida <i>Inés Jacob, Joseba Abaitua, Josu Diaz, Josu Gómez, Koldo Ocina</i>	305

Demostraciones
 Análisis y expansión de
Alberto Ruiz, Paloma
 ANTRO: Un sistema de
Daniel Casanova, Xav
Gema Pérez, David Tr
 Diccionario electrónico
Santiago Fernández Lan
 EGEO: La estructura geo
Ignacio González, Sergi
 El uso de editorial de herr
Adán Cassan, Sergi Cerv
 Gestión flexible de diálogo
Luis Rodrigo Aguado, An
 Llajú: Un sistema de recu
Fernando Martínez Santi
Maite Martín Valdivia, M